

MPPT
Solar
Charge
Controller

AM4860N

Negative Grounded Model



Key Figures:

- ◆ 12/24/36/48 V battery system auto recognition
- ◆ 150 Voc max PV input voltage
- ◆ 60 A max charge current
- ◆ 3.2 KW max PV input power
- ◆ 300 days max data logging
- ◆ 0.3 W max self power consumption

AM4860N is a solar controller with advanced Maximum Power Point Tracking (MPPT) technology, mainly used in small & medium size solar stand alone power systems up to 3.2KW. Additionally, it's a negative grounded model, meets the electrical wiring standard that is widely required in solar power system in North America.

Advanced Maximum Power Point Tracking (MPPT) Technology

- Fast MPPT start with ultra fast of sweeping of the entire V-I curve
- Smart MPPT algorithm ensures a better tracking in multiple power points
- High PV harvest performance in weak sunlight conditions
- Excellent peak efficiency exceeds 98%

High Quality & Functions

- No cooling fan: over rating size heating sink
- Over rating electronic components to minimize the power loss from heating
- Full charge power output up to 45°C
- Compensates battery charge voltages with use of temperature sensor
- LCD screen display: key operation for parameter settings
- Lead-acid AGM/GEL/Flooded & Lithium batteries supportable


Reliable Electronic Protections

- Advanced protections for battery charge & discharge
- Over-heating protection by power derating if temperature is high
- Allow max 25% exceeding rated power without controller damage
- Extensive protections including PV reverse polarity & reverse current protection

Extensive Device Functions

- RS485 port for Modbus communication
- External port for multiple devices parallel use
- Extra 20A DC load output control with various of load modes
- External Bluetooth module connection for APP operation
- External remote LCD display connection

Controller Parameter	Value
Model No.	AM4860N
System Wiring Grounded	Negative Grounded
Battery System Voltage	12V/24V/36V/48V Auto (FLD/GEL/SLD) Manual (Li/User)
No-load Loss	12ma (12V), 10ma (24V), 8ma (36V), 6ma (48V)
Max Solar Input Voltage	<150Voc
Rated Solar Charge Current	60A
Max Solar Input Power	900W/12V 1800W/24V 2600W/36V 3200W/48V
Light Control Voltage	5V*n
Light Control Delay Time	10s
Max Load Output Current	20A
Operating Temperature	-35°C ~ +45°C
IP Protection	IP32
Net Weight	3.0 kg
Communication Port	RS485
Operating Altitude	≤ 3000 meters
Controller Dimension	280*210*90 mm
Battery Voltages	Battery Parameters
Battery Types	FLDSELGEL(default)USER (adjustable)Li (adjustable)
Equalize Charge Voltage	14.8V*n14.6V*n-Default-
Boost Charge Voltage	14.6V*n14.4V*n14.2V*nDefault: GELDefault: 14.2V*n
Float Charge Voltage	-13.8V*nDefault: GEL-
Boost Charge Recovery Voltage	-13.2V*nDefault: GEL-
Over-discharge Recovery Voltage	-12.6V*nDefault: GEL-
Over-discharge Voltage	-11.1V*nDefault: GELDefault: 11.1V*n
Auto Temperature Compensation	-3mV/2V/°CDefault: GEL-
Accessory List	Package Status
External Temperature Sensor	Yes
Remote LCD Meter	Optional
Bluetooth Module	Optional
Parallel Use Module & Cable	Optional
Installation Guidance Paper	Yes
User Manual	Yes



Accessories



App



PV Charge Pro